

AMENDMENTS TO THE CLAIMS

1. (currently amended) A system for elimination of printing registration errors, comprising:
a processor for computing distortion parameters and an imaging system in
communication with said processor and configured for exposing distorted images,
wherein the processor is programmed for:

receiving input data including paper data, at least one machine parameter and ink
distribution data, the processor calculating image dependent errors from said input data;

receiving at least one fixed error map dependent on machine parameters and
obtained during a calibration run;

predicting registration errors based on the fixed error map and said image
dependent errors; and

computing distortion parameters based on said registration errors for creating distorted
images, and

wherein said imaging system includes means for changing the resolution of an
image.

2. (canceled)

3. (previously presented) The system of claim 1, wherein said ink distribution data for an
image file to be exposed is provided by a low resolution image file derived from said image file.

4. (previously presented) The system of claim 1, where said imaging system includes a
strobe card configured for changing timing signals.

10/089.725
11:90898.01

- 2 -

5. (canceled)
6. (previously presented) A method for eliminating printing registration errors in a system comprising a processor for computing distortion parameters and an imaging system in communication with said processor and configured for exposing distorted images, comprising the steps of:
- receiving input data including paper data, at least one machine parameter and ink distribution data;
 - calculating image dependent errors from said input data;
 - receiving at least one fixed error map dependent on machine parameters and obtained during a calibration run;
 - predicting registration errors based on the fixed error map and said image dependent errors; and
 - computing distortion parameters based on said registration errors for creating distorted images.
7. (previously presented) The method of claim 9, wherein said step of providing a reference image includes providing said reference image in a low resolution file.
8. (original) The method of claim 6, additionally comprising:
- providing a printing member; and
 - placing said distorted image onto said printing member.

10x089.725
11190898 01

- 3 -

9. (previously presented) The method of claim 6, wherein said step of computing includes providing a reference image, calculating errors for substantially all of the pixels for at least one color separation in said reference image, and utilizing at least one of strobe data or data manipulation card in combination with said calculated errors to control the rate of imaging to create a distorted image.

10/089,725
11190898 01

- 4 -